

DESCRIPTION:

Glycol mixture GB08 is a mixture of various aliphatic glycols and alcoholates, which have proven effective in the composition of various modifiers of concrete and construction chemistry in general.

APPLICATION:

It is widely used in the construction industry and the production of concrete modifiers and plasticizers. Delivered in specialized tanks.

Parameter	Method		Unit
Water content	ASTM E 203	21.4	wt. %
Density 20 C	ASTM D 4052	1.1851	kg/l
pH val (1:1 demi)		13.3	
Mono Ethylene Glycol	GC	6.2	wt. %
Di Ethylene Glycol	GC	12.0	wt. %
Tri Ethylene Glycol	GC	21.4	wt. %
Tetra Ethylene Glycol	GC	7.9	wt. %
Penta Ethylene Glycol	GC	0.9	wt. %
Mono Propylen Glycol	GC	2.5	wt. %
Di Propylen Glycol	GC	2.7	wt. %
Tri Propylen Glycol	GC	2.8	wt. %
Tetra Propylen Glycol	GC	1.6	wt. %
Impurities	GC	3.4	wt. %
Ash Content	ASTM D 482	17.2	wt. %

ТОВ «Ворлдкем» / LLC Worldchem

Місцезнаходження: 04128, м. Київ, вул. Академіка Туполева 19, оф.43 Код ЄДРПОУ 43482382
ПІН 434823826578
IBAN UA92 334851 00000000 26007111468 в АТ «ПУМБ»
м. Київ, МФО 334851

Тел.: +38 (044) 499 90 77
Kyivstar: +38 (067) 329 05 15

E-mail: info@worldchem.com.ua